

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously amended) A system for completing a well, comprising:
 - a base pipe comprising a hole;
 - at least one packer in mechanical communication with said base pipe;
 - at least one screen in mechanical communication with said base pipe, wherein said at least one screen is proximate the hole in said base pipe;
 - an isolation pipe concentric within said base pipe and proximate to the hole in said base pipe, wherein an annulus is defined between said base pipe and said isolation pipe;
 - an annular flow valve in mechanical communication with said base pipe and said isolation pipe and adapted to control fluid flow through said annulus above and below said valve;
 - and
 - a tool shiftable valve coupled to the isolation pipe.

2. (Previously amended) The system of claim 1, wherein the annular flow valve is a pressure activated valve.

3-22 (Cancelled)

23. (Previously added) The system of claim 1, further comprising an additional valve coupled to the isolation string, the additional valve comprising a pressure activated valve.

24. (Previously added) The system of claim 1, further comprising a cross-over valve in mechanical communication with the base pipe.

25. (Previously added) The system of claim 1, wherein the tool shiftable valve comprises a sliding sleeve shiftable between an open position and a closed position.

26. (Previously added) The system of claim 25, wherein the system is adapted to be inserted into a well to allow a gravel pack operation to occur prior to a closure of the sleeve to allow operation of the annular flow valve through pressurized fluid.

27. (Previously added) An isolation system, comprising:

an isolation pipe comprising a pressure activated valve coupled to the isolation pipe and a tool shiftable valve coupled to the isolation pipe and in communication with the pressure activated valve.

28. (Previously added) The system of claim 27, wherein the tool shiftable valve comprises a sliding sleeve shiftable between an open position and a closed position.

29. (Previously added) The system of claim 27, wherein the tool shiftable valve is inserted into a well to allow a gravel pack operation to occur prior to closing the tool shiftable valve to allow operation of the pressure activated valve through pressurized fluid.

30. (Previously added) The system of claim 28, wherein the isolation pipe defines at least one port, and wherein the open position of the tool shiftable valve allows fluid flow through the port.

31. (Previously added) The system of claim 27, further comprising:

a base pipe;

the isolation pipe being disposed within the base pipe, defining a volume between the base pipe and the isolation pipe;

the pressure activated valve comprising a valve adapted to allow flow between the volume formed by the isolation pipe and the base pipe and an internal portion of the isolation pipe.

32. (Previously added) The system of claim 26, wherein said pressure activated valve comprises:

an outer sleeve having at least one opening and an inner sleeve, the sleeves being

movable relative to each other and configurable in at least locked-closed,

unlocked-closed, and open configurations, wherein the inner sleeve covers the at

least one opening in the locked-closed and unlocked-closed configurations and the

inner sleeve does not cover the at least one opening in the open configuration; and

a pressure area on at least one of the sleeves, wherein a pressure acting on the pressure

area configures the outer sleeve and inner sleeve between the locked-closed and

unlocked-closed configurations.

33. (Previously added) The system of claim 32, further comprising a lock between the inner sleeve and the outer sleeve that locks the inner sleeve and the outer sleeve in the locked-closed configuration.

34. (Previously added) The system of claim 32, further comprising a spring member adapted to bias the inner sleeve relative to the outer sleeve so that the inner sleeve does not cover the at least one opening of the outer sleeve in the open configuration when the lock is released.

35. (Previously added) The system of claim 32, wherein the inner sleeve comprises at least one opening that is selectably aligned with the at least one opening in the outer sleeve to allow fluid flow therethrough.

36. (Previously added) The system of claim 35, further comprising a production screen, wherein fluid passing through the production screen is communicable with the pressure activated valve and the tool shiftable valve.

37. (Previously added) The system of claim 27, wherein the production screen is wrapped around the outside of the pressure activated valve and the tool shiftable valve.

38. (Previously added) A method for isolating a production zone of a well, comprising:
inserting a pipe into the well, the pipe comprising a pressure activated valve and a tool
shiftable valve;
shifting the tool shiftable valve while the tool shiftable valve is disposed in the well; then
opening the pressure activated valve by pressurized fluid acting on the pressure activated
valve.
39. (Previously added) The method of claim 38, wherein opening the pressure activated
valve occurs while the tool shiftable valve remains in the well.
40. (Previously added) The method of claim 38, further comprising performing a gravel pack
operation on the well while the tool shiftable valve is open and the pressure activated valve is
closed.
41. (Previously added) The method of claim 38, wherein the pipe comprises an isolation
string.
42. (Previously added) The method of claim 38, further comprising allowing production
fluid to flow through the pressure activated valve, the tool shiftable valve, or a combination
thereof.

43. (Previously added) The method of claim 38, wherein shifting the tool shiftable valve comprises using a shifting tool to actuate the tool shiftable valve.

44. (Previously added) The method of claim 38, wherein the pressure activated valve comprises an inner sleeve and an outer sleeve having at least one opening, the sleeves being movable relative to each other in at least two directions and initially secured relative to each other in at least one direction, wherein the opening of the pressure activated valve comprises:

- applying a pressurized fluid to a pressure area on at least one of the sleeves to cause the sleeves to move relative to each other in a first direction;
- reducing pressure to allow the sleeves to move relative to each other in a second direction;
- at least partially uncovering the at least one opening to allow fluid flow therethrough.

45. (Previously added) The method of claim 38, further comprising biasing the sleeves relative to each other with a spring member and allowing the sleeves to move relative to each other in the second direction with the spring member after reducing the pressure.

46. (Previously added) A method for isolating a production zone of a well having a perforated casing, comprising:

- running-in an isolation string into the well, the isolation string comprising a pressure activated valve and a tool shiftable valve;

setting the isolation string in the casing adjacent the perforations in the casing;
shifting the tool shiftable valve with a shifting tool;
stringing a production string into the isolation string; and
opening the pressure activated valve.

47. (Previously added) The method of claim 46, wherein the tool shiftable valve is closed during the opening of the pressure activated valve.

48. (Previously added) The method of claim 46, further comprising performing a gravel pack operation on the well while the tool shiftable valve is open and the pressure activated valve is closed.

49. (Previously added) The method of claim 46, further comprising withdrawing the shifting tool from the well after shifting the tool shiftable valve.

50. (Previously added) The method of claim 46, wherein the isolation string further comprises an annular flow valve, and further comprising opening the annular flow valve and allowing fluid flow into the annular flow valve.

51. (Previously added) The method of claim 50, further comprising allowing fluid flow through the annular flow valve while allowing fluid flow through the pressure activated valve into an internal portion of the isolation pipe.

52. (Previously added) The method of claim 50, further comprising opening the annular flow valve with a pressurized fluid, actuating the pressure activated valve to an unlocked closed position with the pressurized fluid, reducing the pressure of the pressurized fluid to open the pressure activated valve, and allowing fluid flow through the annular flow valve and the pressure activated valve.

53. (Previously added) The method of claim 50, wherein fluid flow through the annular flow valve comprises a fluid from a first zone and the fluid flow through the pressure activated valve comprises a fluid from another zone.

54. (Previously added) The method of claim 53, wherein the pressure activated valve is in fluidic contact with a second annular flow valve and the fluid flow through the pressure activated valve and second annular flow valve comprises the same fluid.